

LIQUIGUARDTM GRIPCOTE X

PROTECTION WITHOUT POLLUTION

A LIQUIGUARD[®] Product
protection without pollution



GripCote-X is a water based, eco-bio friendly coating that has been specifically formulated to provide an effective and lasting non-slip solution for PVC and rubber-backed mats in high traffic, commercial applications. It is composed of a tough and durable polymer that creates a strong bond with most materials. Its water and oil resistant structure will protect the coated surface from slipping, moving or bunching, greatly reducing the incidence of slip or trip and fall accidents. **GripCote-X** promotes spatial stability thus relieving the inconvenience of having to frequently reset the mats in their proper place.

GripCote-X replaces double-sided tapes and the like with a more effective and lasting solution that can be easily brushed, rolled or sprayed on to the mats when used on larger surfaces. Additionally, unlike tapes, **GripCote-X** will not lose its effectiveness over time and will not leave a sticky residue or transfer to the substrate.



GripCote-X will reduce movement and provide excellent slip resistance on almost any type of substrate including *ceramic tiles, fiberglass, marble, granite, metal, carpets, tubber, vinyl and wood*. It offers a preferable alternative to the various 'sticky' coatings currently used to provide slip resistance and improved grip. In addition, **GripCote-X** will not stain or mar the surface it comes in contact with and will help with care and maintenance of the mat it has been applied to. When applied to washable mats, **GripCote-X** can withstand up to 20 wash cycles in industrial washing machines when low alkaline detergents are used.

Application: **GripCote-X** is easy to apply using a soft bristle or foam brush, paint roller or HVLP spray device. Lightly stir the **GripCote-X** container prior to use. The target surface should be free of dirt, debris and any type of oil or grease, prior to application. The coating has blue/grey appearance, applies easily and will dry to a black finish. The **GripCote-X** coated object will be ready for use within 4-6 hours after application, depending upon the ambient temperature. Allow 24 hours or more for full cure before subjecting the article to heavy traffic. Do not apply at temperatures below 50°F.

Coverage: Approximately 400 square feet per gallon.

Important: Avoid heavy buildup, puddling and repeated overlapping of **GripCote-X**. Appropriately mask off areas that need to be kept free **GripCote-X**. Wipe off overruns, spills and splatter immediately with water. Thoroughly clean hands and tools after use with soap and warm water. Observe all personal precautions as you would with any other paint or coating product.